

DURAGRIT

VITRIFIED



DTA 999

TILE AND STONE ADHESIVE

APPLICATIONS

- Ideal for high-rise cladding & projects at heights exceeding 40 feet
- Specifically designed for large-format slabs, ceramic, vitrified, and porcelain tiles, including marble, granite, and natural stones, for interior and exterior wall elevations and floor applications
- Available in white also

*Recommendation: Use fasteners for exterior elevation wall tiles



DTA 888

ELEVATION TILE ADHESIVE

APPLICATIONS

- Specifically designed for large-format slabs, ceramic, vitrified, and porcelain tiles, including marble, granite, and natural stones, for interior and exterior wall elevations and floor applications
- Engineered for vertical applications, it ensures exceptional bond strength, making it ideal for installations at significant heights up to 40 feet.
- Designed for green buildings and projects
- Available in white also.

*Recommendation: Use fasteners for exterior elevation wall tiles



DTA 777

TOUGH BOND TILE ADHESIVE

APPLICATIONS

- Specifically designed for interior and exterior wall and floor installations of large-format slabs, ceramic tiles, vitrified tiles, and porcelain tiles. It is also ideal for the installation of marble, granite, and natural stone on interior walls and floors
- Can also be used for door-window fixing solutions
- Available in white also.



DTA 666

APPLICATIONS

- Suitable for fixing all types of ceramic tiles & vitrified tiles on interior wall/floor surfaces
- Ideal for tile-on-tile & bathroom tiling.



DTA 555

APPLICATIONS

- Suitable for fixing all types of ceramic tiles & porcelain tiles on interior wall/floor surfaces



DTA 444

APPLICATIONS

- Suitable for fixing all types of ceramic tiles & vitrified tiles on interior wall/floor surfaces
- Ideal for tile-on-tile & bathroom tiling.



DTA 333

APPLICATIONS

- Suitable for fixing all types of ceramic tiles & porcelain tiles on interior wall/floor surfaces



EPOXY GROUT Available in part & 2 part (EPOXY)

APPLICATIONS

- For interior/exterior residential and commercial floor/wall surfaces or under water areas such as swimming pools and high traffic areas
- Epoxy Grout is available in two and three Components.
- Available in 5 Kg and 1 Kg packaging.



CEMENT POLYMER GROUT

APPLICATIONS

- For grouting interior/exterior residential and commercial wall & floor surfaces in dry or wet conditions.
- Recommended to use with Admixture of 400ml bottle.



ADMIXTURE

ADVANTAGES

- Improves the flexibility of cement polymer grout
- Enhances strength & durability
- Water resistant
- Easy to Clean
- Resistant to mild acids

High Performance Tile Joint Filler Admixture

PACKING SIZE: 400ml



EXTRA STRONG TILE CLEANER

- ✓ REMOVES STAINS
- ✓ KILLS GERMS
- ✓ PRESERVES AND MAINTAINS TILE PRINT/COLOUR.

ADVANTAGES

- Ceramic tiles/Vitrified Tiles/ Granite/Sanitaryware
- Wall & Floor
- Interior & exterior
- Keep out of the reach of children



BOND-STONE

APPLICATIONS

- Fixing of Marble & Granites in Kitchen, Bathroom and Window Frames
- Staircase Moulding
- Woodworking like Wood to Wood, Wood to Marble and Wood to Glass bonding
- Bonding of Cooling Coils to freezers in Refrigerator
- Various fixing and repair applications
- Metal to Metal bonding in Automotive & Fabrication work
- Hardwood Handicraft application
- Dry wall cladding of Engineered/Sintered Marble
- Packing size 450g, 900g, 1.800g



Dura Fix

APPLICATIONS

- Packing size 20g, 50g



